

Intex EziBase™ Joint Compound

1. Identification

Product Details:

| | |
|---------------------------------------|---|
| Product Code: | CBB2060, CBB2040, CBB2020, CBB2090 |
| Other Name: | Stopping Compound, Stopping Mix or Mud, Joint Taping Compound, Basecoat. |
| Recommended Use: | Base and second coats in plasterboard jointing. |
| Manufacturer/ Supplier By: | <p>Intex Group International Pty Ltd (ACN 163012039) 115 McKellar Way Epping, Victoria, Australia 3076 +61 3 9357 9299 (or 1300 107 108 within Australia)</p> <p>Intex New Zealand Pty Ltd (NZCN 7388136) 13 Mahunga Drive, Mangere Bridge, Auckland 2022, New Zealand +64 6 377 7255 (or 0800 278 276 within New Zealand)</p> <p>13 11 26 (AU Poisons Info Centre) 0800 764 766 (NZ Poisons Info Centre)</p> |

2. Hazardous Identification

| | |
|-------------------------------|---------------------|
| Hazard Classification: | Icons as per below. |
|-------------------------------|---------------------|



WARNING
 Causes skin irritation.
 May cause respiratory irritation.
 Causes serious eye irritation.



DANGER
 May cause cancer.
 Harmful if inhaled.

| | |
|-------------------------------|---|
| Hazard Classification: | Setting compounds and plasters are not classified as Dangerous Good for Transport. |
| HSNO Approval Number: | HSR002545 |
| HSNO Classification: | 6.7A May cause cancer by inhalation. 6.9B Harmful to human target organs or systems. |
| GHS Classification: | Carcinogen – Category 1A. Systemic Target Organ Toxicant, repeated exposure – Category 2. |
| Hazard Statements: | H350 May cause cancer (inhalation). H373 May cause damage. |

3. Composition/Information On Ingredients

| | Chemical Name: | Synonyms: | Proportion Wt%: | Cas Number: |
|---------------------------------|------------------------------|------------------|------------------------|---------------------|
| Ingredients composition: | Calcium Sulphate Hemihydrate | | 35 - 100 | 10034-76-1 |
| | Limestone | | 0 - 50 | 1317-65-3, 471-34-1 |
| | Mica | | 0 - 6 | 12001-26-2 |
| | Clay | | 0 - 4 | 8031-18-3 |
| | Polyvinyl alcohol | | 0 - 4 | 25213-24-5 |
| | Starch | | 0 - 2 | Not available |
| | Modified cellulose | | 0 - 1 | Not available |

4. First Aid Measures

| | |
|----------------------------|--|
| Ingestion: | If gastric disturbance occurs, seek medical advice. This product contains gypsum plaster which hardens when wetted and, if ingested in large quantities, may result in obstruction of the gut, especially the pyloric region. If ingested seek medical advice. |
| Eye contact: | Immediately and carefully flush eyes with water for 15 minutes. If irritation persists, seek medical advice. |
| Skin contact: | Rinse with water, then wash with mild soap and water. If irritation persists, contact a doctor. Never make a cast enclosing any part of the body with this product, the material may harden and become extremely hot causing serious burns. |
| Inhalation of dust: | Remove exposed individual to fresh air immediately. If breathing difficulty persist, seek medical advice immediately. |
| Advice to doctor: | Treat symptomatically. |

5. Fire Fighting Measures

| | |
|--|---|
| Flammability: | Not combustible under normal conditions of storage and use. |
| Suitable extinguishing media: | Use extinguishing media appropriate for surrounding fire. |
| Hazards from combustion: | Stable under normal temperature and pressure. At temperatures around 800°C, carbon dioxide may be emitted, due to decomposition of limestone. Product contains low level of organic volatiles, which may be emitted or released in a fire. Thermal decomposition will produce H ₂ O, CO ₂ , CO, and acetic acid. Could produce minor amounts of vinyl acetate monomers when temperature is above 175°C. |
| Protective precautions and equipment for fire fighters: | Appropriate firefighting equipment is required. |
| HAZCHEM Code: | Not allocated. |

6. Accidental Release Measures

| | |
|------------------------------|--|
| Emergency Procedures: | Use normal clean up procedure. Spilled material can produce slippery conditions, be cautious to avoid falling. Wear appropriate protective equipment. Shovel material from spillage into a waste container for disposal. Never discharge directly into drains, water courses or sewers. In the event of a major spill prevent spillage from entering drains, sewers, or water courses. |
|------------------------------|--|

7. Handling & Storage

| | |
|---------------------------|--|
| Handling: | Minimise exposures in accordance with good hygiene practice. During handling wear the appropriate respiratory, eye and skin protection. Clean up any dust and if warranted as per environmental conditions, refer section 2 & 8 of this SDS. Avoid dust contact with eyes and skin. Wear the appropriate eye and skin protection against dust. |
| Storage: | Store in a dry cool and well ventilated areas and at a temperature below 30°C. Keep from freezing. Clean up any spilt dust immediately. Safe storage of this product is required when in bulk storage. |
| Hygiene: | Do not drink, eat, or smoke when using this product. Wash hands, face and remove contaminated clothing or coveralls before eating and after work has been completed. |
| Incompatibilities: | Not applicable. |

8. Exposure Controls/Personal Protection

| | |
|--------------------------------|--|
| Engineering Controls: | All work should be carried out in such a way as to minimise dust generation and exposure to dust. Where operations generate airborne dust, use mechanical ventilation or dust extraction and collection to keep dust concentrations below permissible exposure limits. Work areas should be cleaned regularly. Dry sweeping should be avoided, Use a vacuum. |
| Personal Protection: | |
| Hand Protection: | Use of protective gloves suitable for the risk associated with the task being performed. Nitrile, leather, or neoprene gloves are recommended. Refer Australian/New Zealand Standard AS/NZS 2161 for more information. |
| Skin Protection: | Use protective clothing where skin contact may occur. Refer Australian/New Zealand Standard AS/NZS 4501 for occupational clothing. Remove any contaminated clothing or coveralls after use to avoid prolonged contact with the skin and inhalation of dust from clothing. When mixed with water, this material hardens and then becomes hot. DO NOT attempt to make a cast enclosing any part of the body using this material. Failure to follow these instructions may cause severe burns that may require surgical removal of affected tissue. Direct, prolonged, or repeated contact with skin can result in abrasions. Rinse with water until free of material to avoid abrasions, then wash skin thoroughly with mild soap and water. May dry skin. If irritation persists, consult a doctor. |
| Respiratory Protection: | Use eye and face protectors for protection against dust. Safety glasses with top and side shields or goggles. Do not wear contact lenses. Refer Australian/New Zealand Standard AS/NZS 1337 for more information. |
| Other Information: | Personal Protective Equipment used must be impervious to the substance. Do not eat, smoke, or drink where material is handled, processed, or stored. Always wash hands carefully before eating or smoking. Handle in accordance with safe industrial hygiene practices. Wash work clothes regularly and separately to other clothes. |

9. Physical & Chemical Properties

| | |
|---|-----------------------------|
| Appearance: | Fine cream coloured powder. |
| Odour: | Low odour |
| pH: | 8 |
| Vapour Pressure: | NA |
| Vapour Density: | NA |
| Boiling Point/Range (°C): | 100°C |
| Freezing/Melting Point (°C): | 0°C |
| Solubility in water: | Soluble |
| Packed Bulk Density: | 1 |
| FLAMMABILITY: | Not flammable |
| Additional Properties | |
| Evaporation Rate: % Volatiles: | < 2% |
| Volatile Organic Compounds Content: | < 40g/L |
| Respirable crystalline silica content: | < 0.1% |

10. Stability & Reactivity

| | |
|--|--|
| Chemical Stability: | Stable. |
| Hazardous Decomposition Products: | Stable under normal conditions of temperature and pressure. At temperatures around 800°C, carbon dioxide may be emitted, due to decomposition of limestone. Product contains low level of organic volatiles, which may be emitted or released in application processes involving the use of heat. Vent all ovens and process vessels to the outside atmosphere. Thermal decomposition will produce H ₂ O, CO ₂ , CO, and acetic acid. Could produce minor amounts of vinyl acetate monomers when temperature is above 175°C. |
| Conditions to avoid: | Freeze, thaw, heat. |
| Hazardous polymerization: | Will not occur. |

11. Toxicological Information

| | |
|--|--|
| Health Effects: Acute (short term) | Direct contact may cause eye, skin and/or respiratory irritation. |
| Swallowed: | Not established. |
| Skin: | Dryness of skin. |
| Health Effects: Chronic (long term) | Prolonged exposure and inhalation to air borne free respirable crystalline silica can result in lung disease (<i>i.e. silicosis</i>) and/or lung cancer. |

12. Ecological & Information

| | |
|---------------------------------------|--|
| Eco-toxicity: | No known adverse ecological effects. |
| Persistence and Degradability: | Will form sludge when made wet. Will dry hard on exposure to sun/heat. |
| Mobility: | Lumpy and sludge like when damp. Solid when dry. |

13. Disposal Considerations

| | |
|------------------------------|--|
| Disposal Information: | Dispose to standard landfill. Do not flush down drains. Product can set and block the drain. |
|------------------------------|--|

14. Transport information

| | |
|--------------------------------------|--|
| DG Class: | Not regulated |
| Subsidiary Risk 1: | Not applicable |
| Packaging Group: | Not applicable |
| HAZCHEM code:: | Not allocated |
| Marine Pollutant: | Not applicable |
| Special Precautions for User: | Prevent bags from exposure to damp conditions. |

15. Regular Information

| | |
|--|--|
| | This product is an approved substance under the Hazardous Substances and New Organisms Act (HSNO). Approval code: HSR002545: Construction Products (Toxic [6.7A]) Group Standard 2006. Health & Safety at Work Act 2015 and the Health and Safety at Work (General Risk and Workplace Management) Regulations 2016 – refer Worksafe guidance for dust and respirable Silica in the workplace. The NZ Workplace Exposure Standards Effective from 2016, published by WorkSafe NZ. |
|--|--|

16. Other Information

Keep out of reach of children.

Do not attempt to make a cast enclosing any part of the body using this material. It is not suitable for this use. Where a dust inhalation risk exists to others, consider isolating the work area whilst the product is being worked and generating dust. If isolation is not possible then other persons who may be potentially exposed to dust should use personal protection as detailed in section 8 of this SDS. The full Safety Data Sheet (SDS), or a condensed version, must be readily accessible to people who may handle, or be exposed to, the hazardous substance such as workers and emergency services personnel. The information contained in this document is based on data which, to the best of our knowledge, was accurate and reliable at the time of preparation, no responsibility can be accepted by Intex Group International Pty Ltd. for errors and omissions. The provision of this information should not be construed as a recommendation to use any of our products in violation of any patent rights or in breach of any statute or regulation. Users are advised to make their own determination as to the suitability of this information in relation to their particular purposes and specific circumstances.

DISCLAIMER OF LIABILITY

The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in anyway connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable. Accordingly, Intex will not be responsible for damages resulting from use of or reliance upon this information. Prepared by **Intex Group International Pty Ltd.**

End of SDS.
